## ROCKWELL DECK MOUNTED TAPS, HIGH SPOUT WITH US WASTE- US

Rockwell deck mounted basin taps with high spout, for use with a US basin, please check the waste size is compatible. The crossheads are available in either all metal or Rockwell colored ceramic: lilac/Bonbon, orange/Squash, black/Graphite/Ink, white/Snowdrop, grey/Seattle, green/Willow, blue/Powder, yellow/Sherbet, red/Lipstick and pale pink/Conch. We also offer a color matching service. Please contact the office for further information. Manufactured in England.



Deck thickness maximum: 1 3/4" Drain depth maximum: 2 1/4"

Drain hole diameter minimum: 1 5/16"

Drain style: pop-up

Valve fittings hole diameter: 1 1/8" Spout fittings hole diameter: 1 3/8" Handle spread maximum: 17 3/4" Handle spread minimum: 6" Handle turn angle: 1/4 turn

Overall height: 9"

Inlet connection size: 1/2" NPT Inlet connection type: Male

Number of Holes: 3 Primary material: brass

Flow restriction: supplied with a 1.2 US

GPM flow regulator Spout swivel: no Valve material: brass

Suggested application: basin Water pressure maximum: 84 psi Water pressure minimum: 14 psi Water pressure recommended: 28 psi

## **Product Notes**

All dimensions are based on original specifications and are subject to change

and variation.







