

ROCKWELL DECK MOUNTED TAPS, LOW SPOUT WITH UK WASTE - US

Rockwell deck mounted basin taps with low spout, for use with a UK/European basin, please check the waste size (minimum 44mm/1 3/4" diameter) is compatible. The crossheads are available in either all metal or Rockwell colored ceramic: lilac/Bonbon, orange/Squash, black/Graphite/Ink, white/Snowdrop, grey/Seattle, green/Willow, blue/Powder, yellow/Sherbet, red/Lipstick and pink/Conch. We also offer a color matching service. Please contact the office for further information. Manufactured in England.



Technical Details

Deck thickness maximum: 1 3/4"
Drain depth maximum: 1 3/4"
Drain hole diameter minimum: 1 5/16"
Drain style: Pop-up
Valve fittings hole diameter: 1 1/8"
Spout fittings hole diameter: 1 3/8"
Handle spread maximum: 17 3/4"
Handle spread minimum: 6"
Handle turn angle: 1/4 turn
Height: 3 7/8"
Inlet connection size: 1/2" NPT
Inlet connection type: male
Number of holes: 3
Primary material: brass
Restricted Maximum Flow Rate: 1.2 US gallons per minute
Spout swivel: no
Suggested application: basin
Valve Material: brass
Water Pressure Maximum: 84 psi
Water Pressure Minimum: 14 psi
Water Pressure Recommended: 28 psi

Product Notes

All dimensions are based on original specifications and are subject to change and variation.

