ROCKWELL DECK MOUNTED TAPS, HIGH SPOUT WITH UK WASTE- US

Rockwell deck mounted basin taps with high spout, for use with a UK/European basin, please check the waste size (minimum 44mm/1 ¾" diameter) is compatible. The crossheads are available in either all metal or Rockwell colored ceramic: lilac/Bonbon, orange/Squash, black/Graphite/Ink, white/Snowdrop, grey/Seattle, green/Willow, blue/ Powder, yellow/Sherbet, red/Lipstick and pink/Conch. We also offer a color matching service. Please contact the office for further information. Manufactured in England.

Technical Details

Deck thickness maximum: 1 3/4" Drain depth maximum: 1 1/2" Drain hole diameter minimum: 15/16" Drain style: pop-up Valve fittings hole diameter: 1 1/8" Spout fittings hole diameter: 1 3/8" Handle spread maximum: 17 3/4" Handle spread minimum: 6" Handle turn angle: 1/4 turn Height: 9" Inlet connection size: 1/2" NPT Inlet connection type: male Number of Holes: 3 Primary material: brass Restricted maximum flow rate: 1.2 US gallons per minute Spout swivel: no Suggested application: basin Valve material: brass Water pressure maximum: 84 psi Water pressure minimum: 14 psi Water pressure recommended: 28 psi

Product Notes

All dimensions are based on original specifications and are subject to change and variation.







